

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
26 May 2005 (26.05.2005)


PCT

(10) International Publication Number
WO 2005/047157 A2

- (51) International Patent Classification⁷: **B66B** (74) Agent: **KONE CORPORATION/PATENT DEPARTMENT**; P.O. Box 677, FI-05801 Hyvinkää (FI).
- (21) International Application Number: PCT/FI2004/000668 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 10 November 2004 (10.11.2004) (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (25) Filing Language: Finnish
- (26) Publication Language: English
- (30) Priority Data: 20031647 12 November 2003 (12.11.2003) FI
- (71) Applicant (for all designated States except US): **KONE CORPORATION** [FI/FI]; Kartanontie 1, FI-00330 Helsinki (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **KATTAINEN, Ari** [FI/FI]; Tiilitehtaantie 9, FI-5830 Hyvinkää (FI). **SYRMAN, Timo** [FI/FI]; Pihalammentie 4, FI-05460 Hyvinkää (FI).

[Continued on next page]

(54) Title: ELEVATOR BRAKE AND BRAKE CONTROL CIRCUIT



(57) Abstract: A control circuit for controlling an electromechanical elevator brake, said control circuit comprising at least one brake coil (L1), a direct-voltage source (BR1), a semiconductor switch arrangement and a control unit (CO1) for controlling the circuit, and which circuit further comprises a current measuring unit (Im1) producing current data that can be passed to the control unit (CO1). The circuit comprises at least two semiconductor switches (SW1, SW2), and these can be controlled by the control unit (CO1) in an alternate manner such that the working condition of each switch can be checked in its turn on the basis of feedback data obtained from the current measurement.



Published:

— *without international search report and to be republished upon receipt of that report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.